

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 5/19/2023

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture

Trade name : BLACK CHERRY#TCDL-CFRA-BOWL-NBLC

UFI : HRWU-K492-200N-9RAS
Product code : #TCDL-CFRA-BOWL-NBLC
Type of product : Perfumes, fragrances
Product group : Trade product

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Main use category : Professional use, Industrial use

Industrial/Professional use spec : Industrial

For professional use only : Perfumes, fragrances

Use of the substance/mixture : Perfumes, fragra Function or use category : Odour agents

#### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

The Cosy Owl 20-28 Albert Road, Braintree, Essex CM7 3JQ

Tel: +44 1376 560 348

enquiries@cosyowl.com-www.cosyowl.com

## 1.4. Emergency telephone number

Emergency number : +44 (0) 1376 560348

### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin sensitisation, Category 1 H317 Hazardous to the aquatic environment – Chronic Hazard, Category 3 H412

Full text of H- and EUH-statements: see section 16

## Adverse physicochemical, human health and environmental effects

Harmful to aquatic life with long lasting effects. May cause an allergic skin reaction.

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS07

Signal word (CLP) : Warning

Contains : Aldehyde C-16; Hexyl cinnamic aldehyde; Orange oil ; Linalool; Anisyl acetate; Geranyl acetate; Eugenol; Cyclamal; Damascone Beta; Citronellol Pure; trans-Anethole; Liffarome

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hazard statements (CLP) : H317 - May cause an allergic skin reaction.

H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP) : P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P302+P352 - IF ON SKIN: Wash with plenty of water.

P321 - Specific treatment (see supplemental first aid instruction on this label).

: For professional users only.

#### 2.3. Other hazards

Extra phrases

Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

## **SECTION 3: Composition/information on ingredients**

### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Dipropylene glycol monomethyl ether substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 34590-94-8 EC-No.: 252-104-2	31 – 62	Not classified
Aldehyde C-16	CAS-No.: 77-83-8 EC-No.: 201-061-8 REACH-no: 01-2119967770- 28	2.3 – 4.65	Skin Sens. 1B, H317 Aquatic Chronic 2, H411
Hexyl cinnamic aldehyde	CAS-No.: 101-86-0 EC-No.: 202-983-3 REACH-no: 01-2119533092- 50	2 – 3.95	Skin Sens. 1, H317 Aquatic Chronic 2, H411
Benzaldehyde substance with national workplace exposure limit(s) (BG, FI, HU, LT, LV, PL)	CAS-No.: 100-52-7 EC-No.: 202-860-4 EC Index-No.: 605-012-00-5 REACH-no: 01-2119455540-	1.6 – 3.1	Acute Tox. 4 (Oral), H302
Oxypheylon (Raspberry ketone) crystals	CAS-No.: 5471-51-2 EC-No.: 226-806-4	1.5 – 3	Acute Tox. 4 (Oral), H302
beta-lonone	CAS-No.: 14901-07-6 EC-No.: 238-969-9	1.5 – 2.9	Aquatic Chronic 2, H411

# Safety Data Sheet

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Orange oil	CAS-No.: 8008-57-9 EC-No.: 232-433-8 REACH-no: 01-2119493353- 35	1.1 – 2.25	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Verdox	CAS-No.: 88-41-5 EC-No.: 201-828-7 REACH-no: 01-2119970713- 33	0.9 – 1.85	Aquatic Chronic 2, H411
Linalool	CAS-No.: 78-70-6 EC-No.: 201-134-4 EC Index-No.: 603-235-00-2 REACH-no: 01-2119474016-	0.9 – 1.7	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317
p-Tolualdehyde	CAS-No.: 104-87-0 EC-No.: 203-246-9	0.7 – 1.4	Acute Tox. 4 (Oral), H302
Anisyl acetate	CAS-No.: 104-21-2 EC-No.: 203-185-8	0.6 – 1.1	Skin Sens. 1, H317
Geranyl acetate	CAS-No.: 105-87-3 EC-No.: 203-341-5 REACH-no: 01-2119973480- 35	0.6 – 1.1	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 3, H412
alpha-lonone	CAS-No.: 127-41-3 EC-No.: 204-841-6 REACH-no: 01-2119965149- 27	0.5 – 1.05	Aquatic Chronic 3, H412
Benzyl acetate substance with national workplace exposure limit(s) (BE, DK, ES, IE, LT, LV, PT, RO)	CAS-No.: 140-11-4 EC-No.: 205-399-7 REACH-no: 01-2119638272- 42	0.5 – 1	Aquatic Chronic 3, H412
Eugenol	CAS-No.: 97-53-0 EC-No.: 202-589-1 REACH-no: 01-2119971802- 33	0.3 – 0.6	Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319 Skin Sens. 1B, H317
Cyclamal	CAS-No.: 103-95-7 EC-No.: 203-161-7 REACH-no: 01-2119970582- 32	0.3 – 0.5	Skin Irrit. 2, H315 Skin Sens. 1B, H317 Aquatic Chronic 2, H411
Damascone Beta	CAS-No.: 23726-92-3 EC-No.: 245-843-7	0.2 – 0.4	Skin Irrit. 2, H315 Skin Sens. 1B, H317 Aquatic Chronic 2, H411
Phenoxyethanol substance with national workplace exposure limit(s) (AT, DE, FI, PL, SI, CH)	CAS-No.: 122-99-6 EC-No.: 204-589-7 EC Index-No.: 603-098-00-9 REACH-no: 01-2119488943- 21	0.2 – 0.35	Acute Tox. 4 (Oral), H302 STOT SE 3, H335 Eye Dam. 1, H318

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Allyl caproate	CAS-No.: 123-68-2 EC-No.: 204-642-4 REACH-no: 01-2119983573- 26	0.2 – 0.35	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Aquatic Acute 1, H400 Aquatic Chronic 3, H412
Citronellol Pure	CAS-No.: 106-22-9 EC-No.: 203-375-0 REACH-no: 01-2119453995- 23	0.2 – 0.3	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317
Ethyl acetate substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH); substance with a Community workplace exposure limit	CAS-No.: 141-78-6 EC-No.: 205-500-4 EC Index-No.: 607-022-00-5 REACH-no: 01-2119475103-	0.1 – 0.15	Flam. Liq. 1, H224 Eye Irrit. 2, H319 STOT SE 3, H336
acetophenone substance with national workplace exposure limit(s) (BE, BG, DK, ES, FI, HU, IE, LT, LV, PL, PT, RO)	CAS-No.: 98-86-2 EC-No.: 202-708-7 EC Index-No.: 606-042-00-1 REACH-no: 01-2119533169- 37	0.1 – 0.15	Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319
trans-Anethole	CAS-No.: 4180-23-8 EC-No.: 224-052-0	0.1 – 0.1	Skin Sens. 1B, H317
Liffarome	CAS-No.: 67633-96-9 EC-No.: 266-797-4	0.1 – 0.1	Skin Sens. 1B, H317
decyl alcohol substance with national workplace exposure limit(s) (BG, DE, LT, LV, RO, CH)	CAS-No.: 112-30-1 EC-No.: 203-956-9	0 – 0.0028	Aquatic Chronic 3, H412
Aldehyde C-6 substance with national workplace exposure limit(s) (FI, PL)	CAS-No.: 66-25-1 EC-No.: 200-624-5	0 – 0.0007	Flam. Liq. 3, H226

Full text of H- and EUH-statements: see section 16

## **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

First-aid measures general

First-aid measures after inhalation

First-aid measures after skin contact

First-aid measures after eye contact

First-aid measures after ingestion

: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

: Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.

: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see Get medical advice/attention. on this label). If skin irritation occurs: Get medical advice/attention. Wash with plenty of water/.... Get medical advice/attention. Wash contaminated clothing before reuse. Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.

: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists. Rinse eyes with water as a precaution.

: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Call a poison center or a doctor if you feel unwell.

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

## 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Not expected to present a significant hazard under anticipated conditions of normal use.

Symptoms/effects after skin contact : May cause an allergic skin reaction.

## 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy waterstream.

### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

#### 5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire fighting water from entering the environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Evacuate unnecessary personnel. Avoid contact with skin and eyes.

Avoid breathing dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew

with proper protection. For further information refer to section 8: "Exposure

controls/personal protection".

Emergency procedures : Ventilate area.

#### 6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Soak up spills with inert solids, such as clay or

diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

See Section 8. Exposure controls and personal protection. For further information refer to section 13.

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment. Wash

hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Avoid breathing dust/fume/gas/mist/vapours/spray. No open flames. No smoking.

Avoid contact with skin and eyes.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the

product. Contaminated work clothing should not be allowed out of the workplace. Wash

contaminated clothing before reuse.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep away

from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container closed when not in use. Keep in fireproof place. Store in a well-ventilated place.

Keep cool.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

Storage temperature : 25 °C

Storage area : Store in a well-ventilated place. Store away from heat.

Special rules on packaging : Store in a closed container.

Packaging materials : Do not store in corrodable metal.

#### 7.3. Specific end use(s)

No additional information available

#### **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

#### 8.1.1 National occupational exposure and biological limit values

Dipropylene glycol monomethyl ether (34590-94-8)		
EU - Indicative Occupational Exposure Limit (IOEL)		
IOEL TWA	308 mg/m³	
IOEL TWA [ppm]	50 ppm	
Remark	Possibility of significant uptake through the skin	
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	307 mg/m³ (mixed isomers)	
MAK (OEL TWA) [ppm]	50 ppm (mixed isomers)	
MAK (OEL STEL)	614 mg/m³ (isomers mixtures)	
MAK (OEL STEL) [ppm]	100 ppm (isomers mixtures)	
OEL chemical category	Skin notation	
Belgium - Occupational Exposure Limits		
OEL TWA	308 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL chemical category	Skin, Skin notation	
Bulgaria - Occupational Exposure Limits		
OEL TWA	308 mg/m³	

## Safety Data Sheet

EL TWA [ppm] 50 pp  oatia - Occupational Exposure Limits  // (OEL TWA) [1] 308 m		
/I (OEL TWA) [1] 308 m	ng/m³	
· /	ng/m³	
/I (OFL TWA) [3]		
/I (OEL TWA) [2] 50 pp	om	
EL chemical category Skin r	notation	
prus - Occupational Exposure Limits		
EL TWA 308 m	ng/m³	
EL TWA [ppm] 50 pp	om	
EL chemical category Skin-p	potential for cutaneous absorption	
ech Republic - Occupational Exposure Limits		
EL (OEL TWA) 270 m	ng/m³	
EL chemical category Poten	ntial for cutaneous absorption	
enmark - Occupational Exposure Limits		
EL TWA [1] 309 m	ng/m³	
EL TWA [2] 50 pp	om	
EL chemical category Poten	ntial for cutaneous absorption	
stonia - Occupational Exposure Limits		
EL TWA 308 m	ng/m³	
EL TWA [ppm] 50 pp	om	
EL chemical category Skin r	notation	
Finland - Occupational Exposure Limits		
TP (OEL TWA) [1] 310 m	ng/m³	
TP (OEL TWA) [2] 50 pp	om	
EL chemical category Poten	ntial for cutaneous absorption	
ance - Occupational Exposure Limits		
ME (OEL TWA) 308 m	ng/m³ (restrictive limit)	
ME (OEL TWA) [ppm] 50 pp	om (restrictive limit)	
EL chemical category Risk of	of cutaneous absorption	
Germany - Occupational Exposure Limits (TRGS 900)		
GW (OEL TWA) [1] 310 m	ng/m³ (isomer mixture)	
GW (OEL TWA) [2] 50 pp	om (isomer mixture)	
Gibraltar - Occupational Exposure Limits		
EL TWA 308 m	ng/m³	
EL TWA [ppm] 50 pp	om	
EL chemical category Skin r	notation	
Greece - Occupational Exposure Limits		
EL TWA 600 m	ng/m³	
EL TWA [ppm] 100 p	ррт	
EL STEL 900 m	ng/m³	

# Safety Data Sheet

Dipropylene glycol monomethyl ether (34590-94-8)			
OEL STEL [ppm]	150 ppm		
OEL chemical category	skin - potential for cutaneous absorption		
Hungary - Occupational Exposure Limits			
AK (OEL TWA)	308 mg/m³		
Ireland - Occupational Exposure Limits			
OEL TWA [1]	308 mg/m³ ((2-Methoxymethylethoxy)propanol)		
OEL TWA [2]	50 ppm ((2-Methoxymethylethoxy)propanol)		
OEL STEL	924 mg/m³ (calculated (2-(2-Methoxypropoxy)-1-propanol)		
OEL STEL [ppm]	150 ppm (calculated (2-(2-Methoxypropoxy)-1-propanol)		
OEL chemical category	Potential for cutaneous absorption		
Italy - Occupational Exposure Limits			
OEL TWA	308 mg/m³		
OEL TWA [ppm]	50 ppm		
OEL chemical category	skin - potential for cutaneous absorption		
Latvia - Occupational Exposure Limits			
OEL TWA	308 mg/m³		
OEL TWA [ppm]	50 ppm		
OEL chemical category	skin - potential for cutaneous exposure		
Lithuania - Occupational Exposure Limits			
IPRV (OEL TWA)	300 mg/m³ (2-(2-Methoxypropoxy)-propanol)		
IPRV (OEL TWA) [ppm]	50 ppm (2-(2-Methoxypropoxy)-propanol)		
TPRV (OEL STEL)	450 mg/m³ (2-(2-Methoxypropoxy)-propanol)		
TPRV (OEL STEL) [ppm]	75 ppm (2-(2-Methoxypropoxy)-propanol)		
OEL chemical category	Skin notation		
Luxembourg - Occupational Exposure Limits			
OEL TWA	308 mg/m³		
OEL TWA [ppm]	50 ppm		
OEL chemical category	Possibility of significant uptake through the skin		
Malta - Occupational Exposure Limits			
OEL TWA	308 mg/m³		
OEL TWA [ppm]	50 ppm		
OEL chemical category	Possibility of significant uptake through the skin		
Netherlands - Occupational Exposure Limits			
TGG-8u (OEL TWA)	300 mg/m³		
Poland - Occupational Exposure Limits			
NDS (OEL TWA)	240 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol and 2-(2-Methoxy-1-methylethoxy)propan-1-ol)		
NDSCh (OEL STEL)	480 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-1-ol)		

# Safety Data Sheet

Portugal - Occupational Exposure Limits		
OEL TWA	308 mg/m³ (indicative limit value)	
OEL TWA [ppm] 5	50 ppm (indicative limit value)	
OEL STEL [ppm] 1	150 ppm	
OEL chemical category s	skin - potential for cutaneous exposure indicative limit value	
Romania - Occupational Exposure Limits		
OEL TWA 3	308 mg/m³	
OEL TWA [ppm] 5	50 ppm	
OEL chemical category S	Skin notation	
Slovakia - Occupational Exposure Limits		
NPHV (OEL TWA) [1]	308 mg/m³	
NPHV (OEL TWA) [2] 5	50 ppm	
OEL chemical category	Potential for cutaneous absorption	
Slovenia - Occupational Exposure Limits		
OEL TWA 3	308 mg/m³	
OEL TWA [ppm] 5	50 ppm	
OEL STEL 3	308 mg/m³	
OEL STEL [ppm] 5	50 ppm	
OEL chemical category F	Potential for cutaneous absorption	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA) [1]	308 mg/m³ (indicative limit value)	
VLA-ED (OEL TWA) [2] 5	50 ppm (indicative limit value)	
OEL chemical category s	skin - potential for cutaneous absorption	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	300 mg/m³	
NGV (OEL TWA) [ppm] 5	50 ppm	
KTV (OEL STEL) 4	450 mg/m³	
KTV (OEL STEL) [ppm] 7	75 ppm	
OEL chemical category	Skin notation	
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA) [1]	308 mg/m³	
WEL TWA (OEL TWA) [2] 5	50 ppm	
WEL STEL (OEL STEL)	924 mg/m³ (calculated)	
WEL STEL (OEL STEL) [ppm] 1	150 ppm (calculated)	
WEL chemical category F	Potential for cutaneous absorption	
Norway - Occupational Exposure Limits		
Grenseverdi (OEL TWA) [1]	300 mg/m³	
Grenseverdi (OEL TWA) [2] 5	50 ppm	
Korttidsverdi (OEL STEL) 3	375 mg/m³ (value calculated)	

# Safety Data Sheet

Dipropylene glycol monomethyl ether (34590-94-8)			
Korttidsverdi (OEL STEL) [ppm]	75 ppm (value calculated)		
OEL chemical category	Skin notation		
Switzerland - Occupational Exposure Limits			
MAK (OEL TWA) [1]	300 mg/m³ (aerosol, vapour)		
MAK (OEL TWA) [2]	50 ppm (aerosol, vapour)		
KZGW (OEL STEL)	300 mg/m³ (aerosol, vapour)		
KZGW (OEL STEL) [ppm]	50 ppm (aerosol, vapour)		
USA - ACGIH - Occupational Exposure Limits			
ACGIH OEL TWA [ppm]	100 ppm		
ACGIH OEL STEL [ppm]	150 ppm		
ACGIH chemical category	Skin - potential significant contribution to overall exposure by the cutaneous route		
Benzaldehyde (100-52-7)			
Bulgaria - Occupational Exposure Limits			
OEL TWA	5 mg/m³		
Finland - Occupational Exposure Limits			
HTP (OEL TWA) [1]	4.4 mg/m³		
HTP (OEL TWA) [2]	1 ppm		
HTP (OEL C)	17.4 mg/m³		
HTP (OEL C) [ppm]]	4 ppm		
Hungary - Occupational Exposure Limits			
AK (OEL TWA)	5 mg/m³		
CK (OEL STEL)	10 mg/m³		
Latvia - Occupational Exposure Limits			
OEL TWA	5 mg/m³		
Lithuania - Occupational Exposure Limits			
IPRV (OEL TWA)	5 mg/m³		
Poland - Occupational Exposure Limits			
NDS (OEL TWA)	10 mg/m³		
NDSCh (OEL STEL)	40 mg/m³		
Benzyl acetate (140-11-4)			
Belgium - Occupational Exposure Limits			
OEL TWA	62 mg/m³		
OEL TWA [ppm]	10 ppm		
Denmark - Occupational Exposure Limits			
OEL TWA [1]	61 mg/m³		
OEL TWA [2]	10 ppm		
Ireland - Occupational Exposure Limits			
OEL TWA [2]	10 ppm		

# Safety Data Sheet

Benzyl acetate (140-11-4)			
OEL STEL [ppm]	30 ppm (calculated)		
Latvia - Occupational Exposure Limits			
OEL TWA	5 mg/m³		
Lithuania - Occupational Exposure Limits			
IPRV (OEL TWA)	5 mg/m³		
Portugal - Occupational Exposure Limits			
OEL TWA [ppm]	10 ppm		
OEL chemical category	A4 - Not Classifiable as a Human Carcinogen		
Romania - Occupational Exposure Limits			
OEL TWA	50 mg/m³		
OEL TWA [ppm]	8 ppm		
OEL STEL	80 mg/m³		
OEL STEL [ppm]	13 ppm		
Spain - Occupational Exposure Limits			
VLA-ED (OEL TWA) [1]	62 mg/m³		
VLA-ED (OEL TWA) [2]	10 ppm		
USA - ACGIH - Occupational Exposure Limits			
ACGIH OEL TWA [ppm]	10 ppm		
ACGIH chemical category	Not Classifiable as a Human Carcinogen		
Phenoxyethanol (122-99-6)			
Austria - Occupational Exposure Limits			
MAK (OEL TWA)	110 mg/m³		
MAK (OEL TWA) [ppm]	20 ppm		
MAK (OEL STEL)	110 mg/m³		
MAK (OEL STEL) [ppm]	20 ppm		
OEL C	110 mg/m³		
OEL C [ppm]	20 ppm		
Finland - Occupational Exposure Limits			
HTP (OEL TWA) [1]	110 mg/m³		
HTP (OEL TWA) [2]	20 ppm		
HTP (OEL STEL)	290 mg/m³		
HTP (OEL STEL) [ppm]	50 ppm		
OEL chemical category	Potential for cutaneous absorption		
Germany - Occupational Exposure Limits (TRGS 90	00)		
AGW (OEL TWA) [1]	5.7 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)		
AGW (OEL TWA) [2]	1 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)		

# Safety Data Sheet

Phenoxyethanol (122-99-6)			
Poland - Occupational Exposure Limits			
NDS (OEL TWA)	230 mg/m³		
Slovenia - Occupational Exposure Limits			
OEL TWA	5.7 mg/m³		
OEL TWA [ppm]	1 ppm		
OEL STEL	5.7 mg/m³		
OEL STEL [ppm]	1 ppm		
Switzerland - Occupational Exposure Limits			
MAK (OEL TWA) [1]	110 mg/m³ (aerosol, vapour)		
MAK (OEL TWA) [2]	20 ppm (aerosol, vapour)		
KZGW (OEL STEL)	110 mg/m³ (aerosol, vapour)		
KZGW (OEL STEL) [ppm]	20 ppm (aerosol, vapour)		
Ethyl acetate (141-78-6)			
EU - Indicative Occupational Exposure Limit (IOEL)			
IOEL TWA	734 mg/m³		
IOEL TWA [ppm]	200 ppm		
IOEL STEL	1468 mg/m³		
IOEL STEL [ppm]	400 ppm		
Austria - Occupational Exposure Limits			
MAK (OEL TWA)	734 mg/m³		
MAK (OEL TWA) [ppm]	200 ppm		
MAK (OEL STEL)	1468 mg/m³		
MAK (OEL STEL) [ppm]	400 ppm		
Belgium - Occupational Exposure Limits			
OEL TWA	734 mg/m³		
OEL TWA [ppm]	200 ppm		
OEL STEL	1468 mg/m³		
OEL STEL [ppm]	400 ppm		
Bulgaria - Occupational Exposure Limits			
OEL TWA	734 mg/m³		
OEL TWA [ppm]	200 ppm		
OEL STEL	1468 mg/m³		
OEL STEL [ppm]	400 ppm		
Croatia - Occupational Exposure Limits	Croatia - Occupational Exposure Limits		
GVI (OEL TWA) [1]	734 mg/m³		
GVI (OEL TWA) [2]	200 ppm		
KGVI (OEL STEL)	1468 mg/m³		
KGVI (OEL STEL) [ppm]	400 ppm		

# Safety Data Sheet

Ethyl acetate (141-78-6)		
Cyprus - Occupational Exposure Limits		
OEL TWA	734 mg/m³	
OEL TWA [ppm]	200 ppm	
OEL STEL	1468 mg/m³	
OEL STEL [ppm]	400 ppm	
Czech Republic - Occupational Exposure Limits		
PEL (OEL TWA)	700 mg/m³	
Denmark - Occupational Exposure Limits		
OEL TWA [1]	540 mg/m³	
OEL TWA [2]	150 ppm	
Estonia - Occupational Exposure Limits		
OEL TWA	500 mg/m³	
OEL TWA [ppm]	150 ppm	
OEL STEL	1100 mg/m³	
OEL STEL [ppm]	300 ppm	
Finland - Occupational Exposure Limits		
HTP (OEL TWA) [1]	730 mg/m³	
HTP (OEL TWA) [2]	200 ppm	
HTP (OEL STEL)	1470 mg/m³	
HTP (OEL STEL) [ppm]	400 ppm	
France - Occupational Exposure Limits		
VME (OEL TWA)	1400 mg/m³	
VME (OEL TWA) [ppm]	400 ppm	
Germany - Occupational Exposure Limits (TRGS 90	0)	
AGW (OEL TWA) [1]	730 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)	
AGW (OEL TWA) [2]	200 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)	
Gibraltar - Occupational Exposure Limits		
OEL TWA	200 mg/m³	
OEL TWA [ppm]	734 ppm	
OEL STEL	400 mg/m³	
OEL STEL [ppm]	1468 ppm	
Greece - Occupational Exposure Limits		
OEL TWA	734 mg/m³	
OEL TWA [ppm]	200 ppm	
OEL STEL	1468 mg/m³	
OEL STEL [ppm]	400 ppm	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	734 mg/m³	

# Safety Data Sheet

Ethyl acetate (141-78-6)		
CK (OEL STEL)	1468 mg/m³	
OEL chemical category	Sensitizer	
Ireland - Occupational Exposure Limits		
OEL TWA [1]	734 mg/m³	
OEL TWA [2]	200 ppm	
OEL STEL	1468 mg/m³	
OEL STEL [ppm]	400 ppm	
Italy - Occupational Exposure Limits		
OEL TWA	734 mg/m³	
OEL TWA [ppm]	200 ppm	
OEL STEL	1468 mg/m³	
OEL STEL [ppm]	400 ppm	
Latvia - Occupational Exposure Limits		
OEL TWA	200 mg/m³	
OEL TWA [ppm]	54 ppm	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	500 mg/m³	
IPRV (OEL TWA) [ppm]	150 ppm	
NRV (OEL C)	1100 mg/m³	
NRV (OEL C) [ppm]	300 ppm	
Luxembourg - Occupational Exposure Limits		
OEL STEL	1468 mg/m³	
OEL STEL [ppm]	400 ppm	
Malta - Occupational Exposure Limits		
OEL TWA	734 mg/m³	
OEL TWA [ppm]	200 ppm	
OEL STEL	1468 mg/m³	
OEL STEL [ppm]	400 ppm	
Netherlands - Occupational Exposure Limits		
TGG-8u (OEL TWA)	734 mg/m³	
TGG-15min (OEL STEL)	1468 mg/m³	
Poland - Occupational Exposure Limits		
NDS (OEL TWA)	734 mg/m³	
NDSCh (OEL STEL)	1468 mg/m³	
Portugal - Occupational Exposure Limits		
OEL TWA	734 mg/m³ (indicative limit value)	
OEL TWA [ppm]	200 ppm (indicative limit value)	
OEL STEL	1468 mg/m³ (indicative limit value)	
OEL STEL [ppm]	400 ppm (indicative limit value)	

# Safety Data Sheet

Ethyl acetate (141-78-6)			
Romania - Occupational Exposure Limits			
OEL TWA	400 mg/m³		
OEL TWA [ppm]	111 ppm		
OEL STEL	500 mg/m³		
OEL STEL [ppm]	139 ppm		
Slovakia - Occupational Exposure Limits			
NPHV (OEL TWA) [1]	734 mg/m³		
NPHV (OEL TWA) [2]	200 ppm		
NPHV (OEL C)	1100 mg/m³		
Slovenia - Occupational Exposure Limits			
OEL TWA	734 mg/m³		
OEL TWA [ppm]	200 ppm		
OEL STEL	1468 mg/m³		
OEL STEL [ppm]	400 ppm		
Spain - Occupational Exposure Limits			
VLA-ED (OEL TWA) [1]	734 mg/m³		
VLA-ED (OEL TWA) [2]	200 ppm		
VLA-EC (OEL STEL)	1468 mg/m³		
VLA-EC (OEL STEL) [ppm]	400 ppm		
Sweden - Occupational Exposure Limits			
NGV (OEL TWA)	550 mg/m³		
NGV (OEL TWA) [ppm]	150 ppm		
KTV (OEL STEL)	1100 mg/m³		
KTV (OEL STEL) [ppm]	300 ppm		
United Kingdom - Occupational Exposure Limits			
WEL TWA (OEL TWA) [1]	734 mg/m³		
WEL TWA (OEL TWA) [2]	200 ppm		
WEL STEL (OEL STEL)	1468 mg/m³		
WEL STEL (OEL STEL) [ppm]	400 ppm		
Norway - Occupational Exposure Limits			
Grenseverdi (OEL TWA) [1]	734 mg/m³		
Grenseverdi (OEL TWA) [2]	200 ppm		
Korttidsverdi (OEL STEL)	1468 mg/m³ (value from the regulation)		
Korttidsverdi (OEL STEL) [ppm]	400 ppm (value from the regulation)		
Switzerland - Occupational Exposure Limits			
MAK (OEL TWA) [1]	730 mg/m³		
MAK (OEL TWA) [2]	200 ppm		
KZGW (OEL STEL)	1460 mg/m³		
KZGW (OEL STEL) [ppm]	400 ppm		

# Safety Data Sheet

Ethyl acetate (141-78-6)			
USA - ACGIH - Occupational Exposure Limits			
ACGIH OEL TWA [ppm]	400 ppm		
acetophenone (98-86-2)			
Belgium - Occupational Exposure Limits			
OEL TWA	50 mg/m³		
OEL TWA [ppm]	10 ppm		
Bulgaria - Occupational Exposure Limits			
OEL TWA	5 mg/m³		
Denmark - Occupational Exposure Limits			
OEL TWA [1]	49 mg/m³		
OEL TWA [2]	10 ppm		
Finland - Occupational Exposure Limits			
HTP (OEL TWA) [1]	25 mg/m³		
HTP (OEL TWA) [2]	5 ppm		
Hungary - Occupational Exposure Limits			
AK (OEL TWA)	50 mg/m³		
Ireland - Occupational Exposure Limits			
OEL TWA [1]	49 mg/m³		
OEL TWA [2]	10 ppm		
OEL STEL	147 mg/m³ (calculated)		
OEL STEL [ppm]	30 ppm (calculated)		
Latvia - Occupational Exposure Limits			
OEL TWA	5 mg/m³		
Lithuania - Occupational Exposure Limits			
IPRV (OEL TWA)	5 mg/m³		
OEL chemical category	Skin notation		
Poland - Occupational Exposure Limits			
NDS (OEL TWA)	50 mg/m³		
NDSCh (OEL STEL)	100 mg/m³		
Portugal - Occupational Exposure Limits			
OEL TWA [ppm]	10 ppm		
Romania - Occupational Exposure Limits			
OEL TWA	100 mg/m³		
OEL TWA [ppm]	20 ppm		
OEL STEL	200 mg/m³		
OEL STEL [ppm]	41 ppm		
Spain - Occupational Exposure Limits			
VLA-ED (OEL TWA) [1]	50 mg/m³		
VLA-ED (OEL TWA) [2]	10 ppm		

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

acetophenone (98-86-2)			
USA - ACGIH - Occupational Exposure Limits			
CGIH OEL TWA [ppm] 10 ppm			
decyl alcohol (112-30-1)			
Bulgaria - Occupational Exposure Limits			
OEL TWA	10 mg/m³		
Germany - Occupational Exposure Limits (TRGS 90	0)		
AGW (OEL TWA) [1]	66 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)		
AGW (OEL TWA) [2]	10 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)		
Latvia - Occupational Exposure Limits			
OEL TWA	10 mg/m³		
Lithuania - Occupational Exposure Limits			
IPRV (OEL TWA)	10 mg/m³		
Romania - Occupational Exposure Limits			
OEL TWA	100 mg/m³		
OEL TWA [ppm]	15 ppm		
OEL STEL	200 mg/m³		
OEL STEL [ppm]	30 ppm		
Switzerland - Occupational Exposure Limits			
MAK (OEL TWA) [1]	66 mg/m³ (aerosol, vapour)		
MAK (OEL TWA) [2]	10 ppm (aerosol, vapour)		
KZGW (OEL STEL)	66 mg/m³ (aerosol, vapour)		
KZGW (OEL STEL) [ppm]	10 ppm (aerosol, vapour)		
Aldehyde C-6 (66-25-1)			
Finland - Occupational Exposure Limits			
HTP (OEL STEL)	42 mg/m³		
HTP (OEL STEL) [ppm]	10 ppm		
Poland - Occupational Exposure Limits			
NDS (OEL TWA) 40 mg/m³			
NDSCh (OEL STEL)	80 mg/m³		

## 8.1.2. Recommended monitoring procedures

No additional information available

## 8.1.3. Air contaminants formed

No additional information available

#### 8.1.4. DNEL and PNEC

No additional information available

## 8.1.5. Control banding

No additional information available

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### 8.2. Exposure controls

#### 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

#### 8.2.2. Personal protection equipment

#### Personal protective equipment:

Avoid all unnecessary exposure.

#### Personal protective equipment symbol(s):





### 8.2.2.1. Eye and face protection

#### Eye protection:

Chemical goggles or safety glasses. Safety glasses

#### 8.2.2.2. Skin protection

#### Skin and body protection:

Wear suitable protective clothing

#### Hand protection:

Wear protective gloves.

#### 8.2.2.3. Respiratory protection

#### Respiratory protection:

Wear appropriate mask

#### 8.2.2.4. Thermal hazards

No additional information available

### 8.2.3. Environmental exposure controls

## **Environmental exposure controls:**

Avoid release to the environment.

#### Other information:

Do not eat, drink or smoke during use.

## **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

: Liquid Physical state

Colour : light yellow.amber. Odour characteristic. Odour threshold Not available Not applicable Melting point Not available Freezing point **Boiling point Not available** 

Flammability Not applicable, Combustible liquid

Explosive limits Not available Lower explosion limit Not available Upper explosion limit Not available 78°C Flash point Auto-ignition temperature **Not available** Decomposition temperature Not available рΗ Not available Viscosity, kinematic **Not available** Solubility **Not available** Partition coefficient n-octanol/water (Log Kow) Not available

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Vapour pressure : Not available
Vapour pressure at 50°C : Not available
Density : Not available
Relative density : Not available
Relative vapour density at 20°C : Not available
Particle characteristics : Not applicable

#### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

No additional information available

#### 9.2.2. Other safety characteristics

No additional information available

## **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Combustible liquid. May form flammable/explosive vapour-air mixture.

### 10.3. Possibility of hazardous reactions

Not established.

## 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks.

## 10.5. Incompatible materials

Strong acids. Strong bases.

#### 10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide. May release flammable gases.

### **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Dipropylene glycol monomethyl ether (34590-94-8)			
LD50 oral rat 5.35 g/kg			
LD50 dermal rabbit	9500 mg/kg		
Aldehyde C-16 (77-83-8)			
_D50 oral rat 5470 mg/kg			
LD50 dermal rat	> 2000 mg/kg		
Hexyl cinnamic aldehyde (101-86-0)			
LD50 oral rat 3100 mg/kg			
LD50 oral 3100 mg/kg bodyweight			
LD50 dermal rabbit > 3000 mg/kg			

# Safety Data Sheet

Hexyl cinnamic aldehyde (101-86-0)				
LC50 Inhalation - Rat	> 5 mg/l/4h			
Benzaldehyde (100-52-7)				
LD50 oral rat	1292 mg/kg			
LD50 dermal rabbit	> 1250 mg/kg			
Oxypheylon (Raspberry ketone) crystals (547	1-51-2)			
LD50 oral rat	1320 mg/kg			
LD50 dermal rat	> 2000 mg/kg			
beta-lonone (14901-07-6)				
LD50 oral rat	4590 mg/kg			
LD50 oral	3940 mg/kg bodyweight			
Orange oil (8008-57-9)				
LD50 oral rat	4400 mg/kg			
LD50 dermal rabbit	> 5000 mg/kg			
Verdox (88-41-5)				
LD50 oral rat	4600 mg/kg			
LD50 oral	4600 mg/kg bodyweight			
Linalool (78-70-6)				
LD50 oral	2790 mg/kg bodyweight			
p-Tolualdehyde (104-87-0)				
LD50 oral rat	1600 mg/kg			
LD50 oral	1000 mg/kg bodyweight			
Anisyl acetate (104-21-2)				
LD50 dermal rat	> 2000 mg/kg			
Geranyl acetate (105-87-3)				
LD50 oral rat	6330 mg/kg			
alpha-lonone (127-41-3)				
LD50 oral	4590 mg/kg bodyweight			
Benzyl acetate (140-11-4)				
LD50 oral rat	2490 mg/kg			
LD50 oral	2490 mg/kg bodyweight			
LD50 dermal rabbit	> 5000 mg/kg			
Eugenol (97-53-0)				
LD50 oral rat	1930 mg/kg			
LD50 oral	2500 mg/kg bodyweight			
Cyclamal (103-95-7)				
LD50 oral rat	3810 mg/kg			
LD50 oral	3810 mg/kg bodyweight			

## Safety Data Sheet

Cyclamal (103-95-7)				
LD50 dermal rat	> 5000 mg/kg			
Damascone Beta (23726-92-3)				
LD50 oral	2920 mg/kg bodyweight			
Phenoxyethanol (122-99-6)				
LD50 oral rat	1850 mg/kg			
LD50 oral	1394 mg/kg bodyweight			
LD50 dermal rabbit	5 ml/kg			
LC50 Inhalation - Rat	> 0.057 mg/l (Exposure time: 8 h)			
Allyl caproate (123-68-2)				
LD50 oral	300 mg/kg bodyweight			
LD50 dermal rabbit	820 mg/kg			
LD50 dermal	300 mg/kg bodyweight			
LC50 Inhalation - Rat (Vapours)	3 mg/l/4h			
Citronellol Pure (106-22-9)				
LD50 oral rat	3450 mg/kg			
LD50 oral	3450 mg/kg bodyweight			
LD50 dermal rabbit	2650 mg/kg			
LD50 dermal	2650 mg/kg bodyweight			
Ethyl acetate (141-78-6)				
LD50 oral rat	5620 mg/kg			
LD50 dermal rabbit	> 18000 mg/kg			
LC50 Inhalation - Rat [ppm]	4000 ppm/4h			
acetophenone (98-86-2)				
LD50 oral rat	900 mg/kg			
LD50 oral	500 mg/kg bodyweight			
LD50 dermal rat	3300 mg/kg			
LC50 Inhalation - Rat	> 2.13 mg/l (Exposure time: 8 h)			
trans-Anethole (4180-23-8)				
LD50 oral rat	2090 mg/kg			
LD50 dermal rabbit	> 4900 mg/kg			
LC50 Inhalation - Rat	> 5.1 mg/l/4h			
decyl alcohol (112-30-1)				
LD50 oral rat	4720 mg/kg			
LD50 dermal rabbit	3560 mg/kg			
Aldehyde C-6 (66-25-1)				
LD50 oral rat	4890 mg/kg			
LD50 dermal rabbit	> 8100 mg/kg			
Skin corrosion/irritation :	Not classified			

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Serious eye damage/irritation : Not classified

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified Carcinogenicity : Not classified

Benzyl acetate (140-11-4)

IARC group 3 - Not classifiable

**Eugenol (97-53-0)** 

IARC group 3 - Not classifiable

Reproductive toxicity : Not classified STOT-single exposure : Not classified

Phenoxyethanol (122-99-6)

STOT-single exposure May cause respiratory irritation.

**Ethyl acetate (141-78-6)** 

STOT-single exposure May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified
Aspiration hazard : Not classified

Orange oil (8008-57-9)

Hydrocarbon Yes

#### 11.2. Information on other hazards

#### 11.2.1. Endocrine disrupting properties

No additional information available

#### 11.2.2. Other information

Potential adverse human health effects and

symptoms

: Based on available data, the classification criteria are not met

## **SECTION 12: Ecological information**

### 12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term : Not classified

(acute)

Hazardous to the aquatic environment, long-term : Harmful to aquatic life with long lasting effects.

(chronic)

Dipropylene glycol monomethyl ether (34590-94-8) LC50 - Fish [1] > 10000 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static]) EC50 - Crustacea [1] 1919 mg/l (Exposure time: 48 h - Species: Daphnia magna) Aldehyde C-16 (77-83-8) LC50 - Fish [1] 4.2 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static]) Benzaldehyde (100-52-7) LC50 - Fish [1] 10.6 – 11.8 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through]) LC50 - Fish [2] 12.69 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static]) Linalool (78-70-6) EC50 96h - Algae [1] 88.3 mg/l (Species: Desmodesmus subspicatus)

## Safety Data Sheet

**Eugenol (97-53-0)** 

LC50 - Fish [1]	13 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static])			
Phenoxyethanol (122-99-6)				
LC50 - Fish [1]	337 – 352 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])			
LC50 - Fish [2]	366 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])			
EC50 - Crustacea [1]	> 500 mg/l (Exposure time: 48 h - Species: Daphnia magna)			
EC50 72h - Algae [1]	> 500 mg/l (Species: Desmodesmus subspicatus)			
Allyl caproate (123-68-2)				
LC50 - Fish [1]	0.117 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static])			
Ethyl acetate (141-78-6)				
LC50 - Fish [1]	220 – 250 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])			
LC50 - Fish [2]	484 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])			
EC50 - Crustacea [1]	560 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])			
acetophenone (98-86-2)				
LC50 - Fish [1]	162 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])			
LC50 - Fish [2]	155 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])			
decyl alcohol (112-30-1)				
LC50 - Fish [1]	2.2 – 2.5 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])			
LC50 - Fish [2]	4.12 – 6.2 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])			
EC50 - Crustacea [1]	3 mg/l (Exposure time: 48 h - Species: Daphnia magna)			
Aldehyde C-6 (66-25-1)				
LC50 - Fish [1]	12 – 16.5 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])			
12.2. Persistence and degradability				
BLACK CHERRY				
Persistence and degradability	Not established.			
12.3. Bioaccumulative potential				
BLACK CHERRY				
Bioaccumulative potential	Not established.			
Dipropylene glycol monomethyl ether (34590	)-94-8)			
Partition coefficient n-octanol/water (Log Pow)	0.35 (at 25 °C (at pH 7)			
Aldehyde C-16 (77-83-8)				
Partition coefficient n-octanol/water (Log Pow)	2.4 (at 25 °C (cis isomer)			
Benzaldehyde (100-52-7)				
BCF - Fish [1]	(no significant bioaccumulation)			
Partition coefficient n-octanol/water (Log Pow)	1.4 (at 25 °C)			
Oxypheylon (Raspberry ketone) crystals (5471-51-2)				
Partition coefficient n-octanol/water (Log Pow)	1.33 (at 20 °C)			

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

beta-lonone (14901-07-6)				
Partition coefficient n-octanol/water (Log Pow)	1.903 (at 27 °C (at pH 5.7)			
p-Tolualdehyde (104-87-0)				
Partition coefficient n-octanol/water (Log Pow)	2.25			
Anisyl acetate (104-21-2)				
Partition coefficient n-octanol/water (Log Pow)	1.9 (at 35 °C)			
Geranyl acetate (105-87-3)				
Partition coefficient n-octanol/water (Log Pow)	4.04			
alpha-lonone (127-41-3)				
Partition coefficient n-octanol/water (Log Pow)	3.896 (at 25 °C (at pH 7.2)			
Benzyl acetate (140-11-4)				
Partition coefficient n-octanol/water (Log Pow)	1.96 (at 25 °C (at pH 7)			
Eugenol (97-53-0)				
Partition coefficient n-octanol/water (Log Pow)	1.83 (at 30 °C (at pH 5.5)			
Cyclamal (103-95-7)				
Partition coefficient n-octanol/water (Log Pow)	3.4 (at 35 °C)			
Phenoxyethanol (122-99-6)				
Partition coefficient n-octanol/water (Log Pow)	1.107			
Allyl caproate (123-68-2)				
Partition coefficient n-octanol/water (Log Pow)	3.191 (at 20 °C (at pH 5)			
Citronellol Pure (106-22-9)				
Partition coefficient n-octanol/water (Log Pow)	3.41 (at 25 °C)			
Ethyl acetate (141-78-6)				
BCF - Fish [1]	(30 dimensionless)			
Partition coefficient n-octanol/water (Log Pow)	0.73 (at 20 °C (at pH 7)			
acetophenone (98-86-2)				
Partition coefficient n-octanol/water (Log Pow)	1.63 – 1.65			
Liffarome (67633-96-9)				
Partition coefficient n-octanol/water (Log Pow)	3 (at 25 °C)			
decyl alcohol (112-30-1)				
Partition coefficient n-octanol/water (Log Pow)	4.5 (at 25 °C (at pH 6)			
Aldehyde C-6 (66-25-1)				
Partition coefficient n-octanol/water (Log Pow)	2.3 (at 25 °C (at pH 5)			

## 12.4. Mobility in soil

No additional information available

## 12.5. Results of PBT and vPvB assessment

No additional information available

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 12.6. Endocrine disrupting properties

No additional information available

#### 12.7. Other adverse effects

Additional information : Avoid release to the environment.

### **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

Waste treatment methods

Product/Packaging disposal recommendations

Ecology - waste materials HP Code

- : Dispose of contents/container in accordance with licensed collector's sorting instructions.
- : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container in accordance with local/national laws and regulations.
- : Avoid release to the environment.
- : HP3 "Flammable:"
  - flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C;
  - flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air;
  - flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction;
  - flammable gaseous waste: gaseous waste which is flammable in air at 20  $^{\circ}\text{C}$  and a standard pressure of 101.3 kPa;
  - water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;
  - other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.

HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

### **SECTION 14: Transport information**

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID	
14.1. UN number or ID n	14.1. UN number or ID number				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	
14.2. UN proper shippin	g name				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	
14.3. Transport hazard o	class(es)				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	
14.4. Packing group	14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	
14.5. Environmental hazards					
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	
No supplementary information available					

## 14.6. Special precautions for user

#### Overland transport

Not applicable

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### Transport by sea

Not applicable

#### Air transport

Not applicable

#### Inland waterway transport

Not applicable

### Rail transport

Not applicable

## 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## 15.1.1. EU-Regulations

## **REACH Annex XVII (Restriction List)**

EU restriction list (REACH Annex XVII)			
Reference code	Applicable on	Entry title or description	
3(a)	Orange oil ; Ethyl acetate ; Aldehyde C-6	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories and 2, 2.15 types A to F	
3(b)	BLACK CHERRY ; Aldehyde C- 16; Hexyl cinnamic aldehyde; Benzaldehyde; Orange oil; Linalool; p- Tolualdehyde; Anisyl acetate; Geranyl acetate ; Eugenol; Cyclamal; Damascone Beta; Phenoxyethanol; Allyl caproate; Citronellol Pure ; Ethyl acetate; acetophenone; trans- Anethole; Liffarome	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10	
3(c)	BLACK CHERRY ; Aldehyde C- 16; Hexyl cinnamic aldehyde; beta- lonone; Orange oil; Verdox; Geranyl acetate; alpha- lonone; Benzyl acetate; Cyclamal; Damascone Beta; Allyl caproate; decyl alcohol	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1	
40.	Orange oil ; Ethyl acetate ; Aldehyde C-6	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.	

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### **REACH Annex XIV (Authorisation List)**

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

#### **REACH Candidate List (SVHC)**

Contains no substance(s) listed on the REACH Candidate List

#### **PIC Regulation (Prior Informed Consent)**

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

#### **POP Regulation (Persistent Organic Pollutants)**

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

#### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

#### **Explosives Precursors Regulation (2019/1148)**

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

#### **Drug Precursors Regulation (273/2004)**

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

#### 15.1.2. National regulations

#### **France**

Occupational diseases	
Code	Description
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

### Germany

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1).

Storage class (LGK, TRGS 510) : LGK 10 - Combustible liquids.

Joint storage table : IGK 1

LGK 1	LGK 2A	LGK 2B	LGK 3	LGK 4.1A
LGK 4.1B	LGK 4.2	LGK 4.3	LGK 5.1A	LGK 5.1B
LGK 5.1C	LGK 5.2	LGK 6.1A	LGK 6.1B	LGK 6.1C
LGK 6.1D	LGK 6.2	LGK 7	LGK 8A	LGK 8B
LGK 10	LGK 11	LGK 12	LGK 13	LGK 10-13

Joint storage not permitted for : LGK 1, LGK 2A, LGK 5.1A, LGK 6.2, LGK 7.

Joint storage with restrictions permitted for : LGK 4.1A, LGK 4.2, LGK 4.3, LGK 5.1B, LGK 5.1C, LGK 5.2.

Joint storage permitted for : LGK 2B, LGK 3, LGK 4.1B, LGK 6.1A, LGK 6.1B, LGK 6.1C, LGK 6.1D, LGK 8A, LGK 8B,

LGK 10, LGK 11, LGK 12, LGK 13, LGK 10-13.

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

#### **Netherlands**

ABM category : A(2) - toxic for aquatic organisms, may have longterm hazardous effects in aquatic

: None of the components are listed

environment

SZW-lijst van kankerverwekkende stoffen : Orange oil ,Liffarome are listed

SZW-lijst van mutagene stoffen : Orange oil ,Liffarome are listed SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed

Vruchtbaarheid

SZW-lijst van reprotoxische stoffen -

SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

Denmark

Class for fire hazard : Class III-1 Store unit : 50 liter

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Classification remarks : Flammable according to the Danish Ministry of Justice; Emergency management guidelines

for the storage of flammable liquids must be followed

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product

Pregnant/breastfeeding women working with the product must not be in direct contact with

the product

**Switzerland** 

Storage class (LK) : LK 10/12 - Liquids

## 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## **SECTION 16: Other information**

Other information : None.

Full text of H- and EUH-statements:		
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3	
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3	
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4	
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2	
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3	
Asp. Tox. 1	Aspiration hazard, Category 1	
Eye Dam. 1	Serious eye damage/eye irritation, Category 1	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2	
Flam. Liq. 1	Flammable liquids, Category 1	
Flam. Liq. 3	Flammable liquids, Category 3	
H224	Extremely flammable liquid and vapour.	
H226	Flammable liquid and vapour.	
H301	Toxic if swallowed.	
H302	Harmful if swallowed.	
H304	May be fatal if swallowed and enters airways.	
H311	Toxic in contact with skin.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H318	Causes serious eye damage.	
H319	Causes serious eye irritation.	
H331	Toxic if inhaled.	
H335	May cause respiratory irritation.	
H336	May cause drowsiness or dizziness.	
H400	Very toxic to aquatic life.	
H411	Toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

The classification complies with

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

: ATP 12